

## APPENDIX B – Special Regulations for Inshore Racing

---

Special Regulations for inshore racing are intended for use in short races, close to shore in relatively warm and protected waters where adequate shelter and/or effective rescue is available all along the course, held in daylight only.

### Part A Basic

Regulation	Item
1.02	<b>Responsibility of Person in Charge</b>
1.02.1	Under <u>RRS</u> 3 the responsibility for a boat's decision to participate in a race or continue racing is hers alone. The safety of a boat and her crew is the sole and inescapable responsibility of the <i>person in charge</i> who shall do his best to ensure that the boat is fully found, thoroughly seaworthy and manned by an experienced and appropriately trained crew who are physically fit to face all weather. The <i>person in charge</i> shall also assign a person to take over his responsibilities in the event of his incapacitation.
2.04.1	<b>All equipment required by OSR shall:</b> <ul style="list-style-type: none"><li>a) function properly,</li><li>b) be regularly checked, cleaned and serviced,</li><li>c) if it has an expiry date, it will not have exceeded its expiry date whilst racing,</li><li>d) when not in use be stowed in conditions in which deterioration is minimised,</li><li>e) be readily accessible, and</li><li>f) be of a type, size and capacity suitable and adequate for the intended use and size of the boat.</li></ul>
3.02	<b>Watertight and Structural Integrity of a Boat</b>
3.02.1	A boat shall be essentially watertight and all openings shall be capable of being immediately secured. Centreboard or daggerboard trunks and the like shall not open into the interior of a hull except via a watertight maintenance <u>hatch</u> with the opening entirely above the <u>waterline</u> .

### Part B Portable Equipment

A boat shall have:

Regulation	Item
3.23	A strong bucket with a lanyard and of at least 9 L (2.4 US Gal) capacity.
3.24	A compass (a hand-held is acceptable).
4.05	A fire extinguisher required if electrical system, engine or stove on board.

## APPENDIX B – Special Regulations for Inshore Racing

---

- 4.06 An anchor.
- 4.22.3 A lifebuoy with a drogue.
- 4.22.4 A heaving line, no less than 6 mm (1/4") diameter, 15–25 m (50–75') long, readily accessible to cockpit.
- 4.25 A strong, sharp knife, in a securely restrained sheath shall be readily accessible from the deck or a cockpit.

### Each Crewmember shall have:

- | Regulation | Item  |
|------------|---|
| 5.01.1     | <p>A gas inflatable lifejacket which shall comply with <u>ISO 12402-3</u> (Level 150) and have been manufactured after 2011. It shall be fitted with the following, each complying with <u>ISO 12402-3</u> or <u>ISO 12402-8</u>:</p> <ul style="list-style-type: none"><li>a) a manual or automatic gas inflation system,</li><li>b) a ride up prevention system (crotch strap or thigh straps),</li></ul> <p>It shall also:</p> <ul style="list-style-type: none"><li>g) be of the appropriate size range for the <u>crewmember</u> as marked on the PFD, and</li><li>h) have been indelibly marked with the name of the owner or boat.</li></ul> |
| 5.01.4     | <p>The person in charge shall personally check that each lifejacket has been serviced in accordance with the manufacturer's recommendation by an approved service station and that the next service date as marked on the lifejacket has not been exceeded.</p>   |